



HR-S is an electro-mechanical room humidistat for controlling humidification and/or dehumidification in HVAC systems.

- \* 1-step
- \* Protection class IP30
- \* Changeover contact 250 V AC, 5 A
- \* High reliability and accuracy
- \* Setpoint settings can be locked

## Function

The humidistat uses a synthetic element as sensor medium. The synthetic element stretches as the humidity increases and shrinks as the humidity decreases. These changes are transmitted to a microswitch.

The setpoint knob affects the position of the microswitch in relation to the synthetic element. The setpoint can be set at between 20...90% RH.

### Synthetic Element

We have developed a new synthetic element that gives a high accuracy at a low cost.

### Setpoint knob can be locked

In order to eliminate the risk of tampering, the setpoint knob can be locked by means of a locking screw under the cover.

### Typical applications

Can be used to control a humidifier or a dehumidifier or for on/off controlling of a fan. Can also be used to alarm when the humidity exceeds or falls below a pre-set level.

## Technical data

### General

Material casing Polycarbonate

Ambient temperature 0...40°C

Mounting Wall mounting

Protection class IP30



This Product confirms with the requirements of European LVD standards EN 60730-1:2000+A11+A12, EN 60730-2-13:1998+A1 and carries the CE-mark

### Outputs

Changeover contact 250 V AC, 5 A

### Settings

Setpoint 20...90% RH

Hysteresis +/- 4% RH

## Wiring and Dimensions

### Wiring

Humidification Closing contact between terminals 1 and 2

Dehumidification Closing contact between terminals 1 and 3

### Dimensions

