



DMD is a differential pressure transmitter with display, for measuring overpressure, underpressure and differential pressure in neutral gases. The main application is for pressure control in air handling systems

- * Selectable measuring range 0...100, 0...300, 0...500, 0...1000 Pa
- * Output 0...10 V and 4...20 mA
- * LED display
- * Damping of measuring signal is adjustable
- * Zero-point adjustment
- * LON-version available

Function

The differential pressure transmitter DMD is based on microprocessor technology and it has a logical menu system.

Settings of working range, damping, and zero-point adjustment are made using buttons under the lid.

Measuring technique

Pressure measurements are obtained by means of a sensor that uses a ceramic measuring beam. The differential pressure affects a membrane that works directly against the measuring beam. The thick-film resistor is mounted on the bending area of the measuring beam. When the measuring beam bends the resistance value changes and will then be converted to a proportional output signal via built-in electronics.

The small number of moving parts in the transmitter, permits a high degree of accuracy and short response time. Another important quality is that the ceramic element has a very good long-time stability.

Adjustable working range

DMD can easily be set between the working ranges 0...100, 0...300, 0...500, 0...1000 Pa.

Electronical damping

The pressure transmitters have electronical damping to counteract rapid fluctuations in the output signal, this function is adjustable 0...20 s.

Zero-point adjustment

The output can easily be zero-point adjusted, see overleaf.

DMD is supplied complete with connection set containing two pressure outlets and 2 m hose.

Technical data

| | |
|------------------------|----------------------------|
| Supply voltage | 24 V AC/DC +/-10% 50-60 Hz |
| Power consumption | 5 VA |
| Ambient temperature | 0...50°C |
| Ambient humidity | Max 90%RH |
| Medium temperature | 0...70°C |
| Storage temperature | -40...+50°C |
| Maximum overload | 20 kPa |
| Accuracy | +/- 1 % at 20°C |
| Temperature dependence | +/- 0,05% /°C |
| Protection class | IP54 |



This product conforms with the requirements of European EMC standards CENELEC EN 50081-1 and EN 50082-1 and carries the CE mark

Outputs

| | |
|-----------------|--|
| Output | 0...10 V and 4...20 mA, corresponding to selected setpoint |
| Load resistance | > 2 Kohm (0...10 V), < 500 ohm (4...20 mA) |

Settings

| | |
|-----------------------|--|
| Measuring range | 0...100 / 0...300 / 0...500 / 0...999 Pa, selectable |
| Zero-point adjustment | By means of buttons under the lid |
| Electronic damping | 0...20 s, adjustable under the lid |

Connection

| | |
|----------------------|---|
| Electric connections | Screw block terminals. Flexible cable is recommended. |
| Pressure | Hose nippel. For 6 mm hose |

Indication

| | |
|---------|-------------------|
| Display | LED, three digits |
|---------|-------------------|

Settings in the menu system

All settings are made using any of three buttons. Two buttons (Up, Down) are used to scroll upwards and downwards between the possible settings. The third button (Enter) is used to select the alternative which currently appears on the display. If the buttons are left unattended for a period of 10 seconds the menu automatically returns to the running mode.

Settings

Press Enter. The display shows -01.
Press the Up button until the display shows the required menu. Press Enter and the display shows the current reading.
The display alternates between the reading and the menu number.

To obtain another reading press the Up or Down buttons until the required reading appears. Press Enter again to confirm the setting which is then stored in the memory. After that the display automatically returns to normal mode and shows the current pressure.


Should you, after all, not wish to change a reading the menu system automatically returns to running mode if the buttons are left unattended for 10 seconds.

Menus

| | | |
|----------------|-----|------------------------------------|
| Working range | -01 | 0..100 / 300 / 500 / 999 Pa |
| Damping | -03 | 0...20 s |
| Zeropoint adj. | -08 | Press on Enter obtains zero output |

Dimensions and wiring

| | |
|---|---------------------------|
| 1 | 24 V AC/DC |
| 2 | 24 V AC/DC system neutral |
| 3 | Signal neutral |
| 4 | Output 0...10 V DC |
| 5 | Output 4...20 mA |
| 6 | Not in use |
| 7 | Not in use |
| 8 | Not in use |
| 9 | Not in use |



Head Office Sweden

Phone: +46 31 720 02 00
Web: www.regin.se
Mail: info@regin.se

Sales Offices

France: +33 14 171 46 46
Hong Kong: +852 24 07 02 81
Singapore: +65 67 47 82 33



THE CHALLENGER IN BUILDING AUTOMATION